

## ToLEDo LYNX Q

ToLEDo Q 1500LM GR10Q 835 SL

0028070



### Product features

- LED replacement for compact fluorescent Lynx-Q lamps
- 40,000 hours average rated life (L70 F50)
- 3 years warranty
- Quick, simple and safe replacement without rewiring
- Direct retrofit - easiest way to upgrade existing luminaires to LED technology
- Suitable for magnetic ballast/CCG and direct mains 220-240V AC operation
- Low energy consumption and no flickering
- Compact and durable construction
- Minimum and maximum operating temperature: -10°C to 40°C
- Ideal for commercial and residential applications including offices, hotels, restaurants, warehouses, supermarkets, corridors, in addition to living rooms, kitchens and garages
- Warning: ToLEDo Lynx Q lamps are not suitable for operation with electronic ballast/ECG operation. Remove the fluorescent starter when used with magnetic/ CCG ballast.



## PRODUCT OVERVIEW

Produktens namn	ToLEDo Q 1500LM GR10Q 835 SL
Technology	LED
Watt (klassificerad) (W)	12.5
Socket/Bas	GR10q
Armaturklassning	Open
Generella tillämpningar	Hospitality, Logistics & Industry, Residential & Consumer
ETIM Class	EC001959
E-nummer FI	4740788
Warranty	3 years
Ljusflöde (nominellt) (lm)	1500
Färgtemperatur (K)	3500
Färgtemperatur	White
CRI (Ra)	80
Watt (nominell) (W)	12.5
Spänning (V)	230
Genomsnittlig (nominell) (timmar)	40000
EAN-kod	5410288280707

## DATA TABLE

### General data

Produktens namn	ToLEDo Q 1500LM GR10Q 835 SL
Technology	LED
Watt (klassificerad) (W)	12.5
Socket/Bas	GR10q
Armaturklassning	Open
Generella tillämpningar	Hospitality, Logistics & Industry, Residential & Consumer
Performance ambient temperature Tq (°C)	25

## ToLEDo LYNX Q

ToLEDo Q 1500LM GR10Q 835 SL

0028070

ETIM Class	EC001959
E-nummer FI	4740788
Warranty	3 years

### Optical data

Ljusflöde (nominellt) (lm)	1500
Färgtemperatur (K)	3500
Färgtemperatur	White
CRI (Ra)	80
Lumenbibehållning i slutet av nominell livslängd (lm)	70

### Electrical data

Watt (nominell) (W)	12.5
Starttid (max) (s)	<0.5
Uppvärmningstid till 60 % av fullt ljus (max) (s)	<0.5
Spänning (V)	230
Lampans effektfaktor	0.9
No. Of switching cycles before premature failures	>100000
Inrush Current (A)	12
Nominal Frequency (Hz)	50/60Hz

### Lifetime data

Genomsnittlig (nominell) (timmar)	40000
Genomsnittlig livslängd (klassificerad) (h)	40000

### Physical data

Längd (mm)	201
Nominal Product Diameter (mm)	188
Vikt (kg)	0.155

### Packaging

Förpackningsbeskrivning	Carton
EAN-kod	5410288280707
Förpackningens enkellängd (cm)	20.4
Förpackningens enkelbredd (cm)	3.5
Förpackningens enkelhöjd (cm)	19.1
DUN14 (outer)	15410288280704
Units per outer package	6
Packaging outer length / height (cm)	42.0
Packaging outer width (cm)	11.4
Packaging outer depth (cm)	20.8

### Safety data

Rengöringsinstruktioner för trasiga lampor	Not applicable
Lampa för särskilda användningsområden	Nr

## ToLEDo LYNX Q

*ToLEDo Q 1500LM GR10Q 835 SL*

0028070

---

Endast för användning i torra miljöer	JA
Inte lämplig för användning i hemmet	JA
Safety message	Not Suitable for totally enclosed fixtures