

PAR56 LED PAR56 LED RGB 0060540



Product features

By combining high power LED's of red, green and blue, together with an internal microprocessor, the RGB version is capable of generating a full spectrum of colours, creating an enhanced swimming experience. The light source can be operated in a mode of continuous colour changing or fixed at any desired colour by briefly switching off and back on again. This is facilitated by the optional Sylvania remote control and receiver.



PRODUCT OVERVIEW

Product name	PAR56 LED RGB
Technology	LED
Watt (Rated) (W)	10
Туре	PAR 56
Cap/Base	Screw Terminal
Fixture rating	Enclosed
Environment	External
General application	Hospitality, Residential & Consumer, Retail
ETIM Class	N/A
E-number SE	8290020
Luminous flux (Im)	300
LOR (%)	100
Light colour	RGB
Colour Code	N/A
Beam Angle (°)	40
Wattage (W)	10
Control gear type	Other
Average life (Nominal) (h)	25000
IP rating	IP68
Product EAN number	5410288605401

DATA TABLE

General data	
Product name	PAR56 LED RGB
Technology	LED
Watt (Rated) (W)	10
Туре	PAR 56
Cap/Base	Screw Terminal
Fixture rating	Enclosed
Environment	External
General application	Hospitality, Residential & Consumer, Retail
Operating temperature range (°C)	-10°C+55°C



PAR56 LED PAR56 LED RGB 0060540


ETIM Class	N/A
E-number SE	8290020
	020020
Optical data	
Luminous flux (Im)	300
Ambient temperature for maximum luminous flux (°C)	25
LOR (%)	100
Light colour	RGB
Colour Code	N/A
Adjustable chromaticity	N
Beam Angle (°)	40
Electrical data	
Wattage (W)	10
Current (A)	0.119
Mains voltage (V)	12V
Lamp power factor	1
Control gear type	Other
Transformer required	Yes
Lifetime data	
Average life (Nominal) (h)	25000
Average life (Rated) (h)	25000
Physical data	
Physical data	1049
IP rating	IP68
IP rating Nominal Product Width (mm)	105
IP rating Nominal Product Width (mm) Cutout Dimensions (W x L in mm or Diameter in mm)	105 170
IP rating Nominal Product Width (mm) Cutout Dimensions (W x L in mm or Diameter in mm) Max. Lamp Diameter (mm) - D	105 170 175
IP rating Nominal Product Width (mm) Cutout Dimensions (W x L in mm or Diameter in mm) Max. Lamp Diameter (mm) - D Weight (kg)	105 170 175 0.552
IP rating Nominal Product Width (mm) Cutout Dimensions (W x L in mm or Diameter in mm) Max. Lamp Diameter (mm) - D	105 170 175
IP rating Nominal Product Width (mm) Cutout Dimensions (W x L in mm or Diameter in mm) Max. Lamp Diameter (mm) - D Weight (kg) Recessed Depth (mm)	105 170 175 0.552
IP rating Nominal Product Width (mm) Cutout Dimensions (W x L in mm or Diameter in mm) Max. Lamp Diameter (mm) - D Weight (kg) Recessed Depth (mm) Packaging	105 170 175 0.552 10
IP rating Nominal Product Width (mm) Cutout Dimensions (W x L in mm or Diameter in mm) Max. Lamp Diameter (mm) - D Weight (kg) Recessed Depth (mm) Packaging Single packaging type	105 170 175 0.552 10 Carton
IP rating Nominal Product Width (mm) Cutout Dimensions (W x L in mm or Diameter in mm) Max. Lamp Diameter (mm) - D Weight (kg) Recessed Depth (mm) Packaging Single packaging type Product EAN number	105 170 175 0.552 10 Carton 5410288605401
IP rating Nominal Product Width (mm) Cutout Dimensions (W x L in mm or Diameter in mm) Max. Lamp Diameter (mm) - D Weight (kg) Recessed Depth (mm) Packaging Single packaging type Product EAN number Packaging single length / height (cm)	105 170 175 0.552 10 Carton 5410288605401 15.0
IP rating Nominal Product Width (mm) Cutout Dimensions (W x L in mm or Diameter in mm) Max. Lamp Diameter (mm) - D Weight (kg) Recessed Depth (mm) Packaging Single packaging type Product EAN number Packaging single length / height (cm) Packaging single width (cm)	105 170 175 0.552 10 Carton 5410288605401 15.0 15.0
IP rating Nominal Product Width (mm) Cutout Dimensions (W x L in mm or Diameter in mm) Max. Lamp Diameter (mm) - D Weight (kg) Recessed Depth (mm) Packaging Single packaging type Product EAN number Packaging single length / height (cm) Packaging single depth (cm)	105 170 175 0.552 10 Carton 5410288605401 15.0 15.0 16.3
IP rating Nominal Product Width (mm) Cutout Dimensions (W x L in mm or Diameter in mm) Max. Lamp Diameter (mm) - D Weight (kg) Recessed Depth (mm) Packaging Single packaging type Product EAN number Packaging single length / height (cm) Packaging single depth (cm) Packaging single depth (cm) DUN14 (outer)	105 170 175 0.552 10 Carton 5410288605401 15.0 15.0 16.3 15410288605408
IP rating Nominal Product Width (mm) Cutout Dimensions (W x L in mm or Diameter in mm) Max. Lamp Diameter (mm) - D Weight (kg) Recessed Depth (mm) Packaging Single packaging type Product EAN number Packaging single length / height (cm) Packaging single length / height (cm) Packaging single depth (cm) DUN14 (outer) Units per outer package	105 170 175 0.552 10 Carton 5410288605401 15.0 16.3 15410288605408 6
IP rating Nominal Product Width (mm) Cutout Dimensions (W x L in mm or Diameter in mm) Max. Lamp Diameter (mm) - D Weight (kg) Recessed Depth (mm) Packaging Single packaging type Product EAN number Packaging single length / height (cm) Packaging single depth (cm) Packaging single depth (cm) DUN14 (outer) Units per outer package Packaging outer length / height (cm)	105 170 175 0.552 10 Carton 5410288605401 15.0 15.0 16.3 15410288605408 6 46.5
IP rating Nominal Product Width (mm) Cutout Dimensions (W x L in mm or Diameter in mm) Max. Lamp Diameter (mm) - D Weight (kg) Recessed Depth (mm) Packaging Single packaging type Product EAN number Packaging single length / height (cm) Packaging single depth (cm) Packaging single depth (cm) DUN14 (outer) Units per outer package Packaging outer length / height (cm) Packaging outer width (cm)	105 170 175 0.552 10 Carton 5410288605401 15.0 16.3 15410288605408 6 46.5 31.5
IP rating Nominal Product Width (mm) Cutout Dimensions (W x L in mm or Diameter in mm) Max. Lamp Diameter (mm) - D Weight (kg) Recessed Depth (mm) Packaging Single packaging type Product EAN number Packaging single length / height (cm) Packaging single depth (cm) Packaging single depth (cm) DUN14 (outer) Units per outer package Packaging outer length / height (cm)	105 170 175 0.552 10 Carton 5410288605401 15.0 15.0 16.3 15410288605408 6 46.5
IP rating Nominal Product Width (mm) Cutout Dimensions (W x L in mm or Diameter in mm) Max. Lamp Diameter (mm) - D Weight (kg) Recessed Depth (mm) Packaging Single packaging type Product EAN number Packaging single length / height (cm) Packaging single depth (cm) Packaging single depth (cm) DUN14 (outer) Units per outer package Packaging outer length / height (cm) Packaging outer length / height (cm) Packaging outer width (cm) Packaging outer width (cm)	105 170 175 0.552 10 Carton 5410288605401 15.0 16.3 15410288605408 6 46.5 31.5
IP rating Nominal Product Width (mm) Cutout Dimensions (W x L in mm or Diameter in mm) Max. Lamp Diameter (mm) - D Weight (kg) Recessed Depth (mm) Packaging Single packaging type Product EAN number Packaging single length / height (cm) Packaging single depth (cm) Packaging single depth (cm) DUN14 (outer) Units per outer package Packaging outer length / height (cm) Packaging outer width (cm)	105 170 175 0.552 10 Carton 5410288605401 15.0 16.3 15410288605408 6 46.5 31.5




PAR56 LED PAR56 LED RGB 0060540

Recommendation for disposal at end of life	Not Applicable
Special purpose lamp	Yes
Suitable for household illumination	No
Safety message	Not suitable for household

PHOTOMETRY





TECHNICAL DRAWINGS

