

# PRODUCT DATASHEET

## LED Switch Batten 8 W 3000 K

**LED SWITCH BATTEN | Slim LED batten luminaires with included switch, joinable for seamless strip lighting**



---

### AREAS OF APPLICATION

- Indoor applications
- Under cabinet lighting
- Accent lighting
- General indoor illumination
- Corridors, entrance areas, stairwells, living rooms, basements
- Cove lighting

---

### PRODUCT BENEFITS

- Little space required thanks to compact dimensions
- Ready for connection due to integrated on/off switch and cable with EU-plug
- Easy and quick electrical connection for light line installation
- Flexible application due to a wide range of available lengths of 300 to 1200 mm.
- Flexible installation in 2 different angles with 2 different mounting options

---

### PRODUCT FEATURES

- Replacement for traditional T8 luminaires
- On/off switch on luminaire
- Polycarbonate housing
- Lifetime: up to 30,000 h
- Color temperature: 3,000 K, 4,000 K
- High luminous efficacy: up to 115 lm/W
- Lengths available: 0.3 m, 0.6 m, 0.9 m, 1.2 m



- Mounting accessories included

**TECHNICAL DATA**

Electrical data

<b>Nominal wattage</b>	8.00 W
<b>Operating mode</b>	Mains voltage
<b>Nominal voltage</b>	220...240 V
<b>Mains frequency</b>	50/60 Hz

Photometrical data

<b>Color temperature</b>	3000 K
<b>Color rendering index Ra</b>	≥80
<b>Light color (designation)</b>	Cool White
<b>Luminous flux</b>	800 lm
<b>Luminous efficacy</b>	100 lm/W
<b>Luminous efficacy of lamp in luminaire</b>	100 lm/W

Dimensions & weight



<b>Length</b>	573.0 mm
<b>Width</b>	22.0 mm
<b>Height</b>	30.0 mm
<b>Product weight</b>	227.00 g

Colors & materials

<b>Body material</b>	Polycarbonate (PC)
<b>Housing color</b>	White
<b>Product color</b>	White
<b>Cover material</b>	Polycarbonate (PC)

Temperatures & operating conditions

<b>Ambient temperature range</b>	-20...40 °C
----------------------------------	-------------

Lifespan

<b>Lifespan</b>	30000 h
-----------------	---------

Additional product data

<b>Mounting type</b>	Surface
----------------------	---------

Capabilities

<b>Dimmable</b>	No
<b>Type of connection</b>	Plug, EU

Certificates & standards

<b>Protection class</b>	II
<b>Type of protection</b>	IP20
<b>Standards</b>	CE/EAC/REACH/RoHS

**EQUIPMENT / ACCESSORIES**

- Equipped with 1.5 m cable and EU plug
- Mounting bracket included
- Fixed connector and flexible connecting cable included



Detail



Detail

**LOGISTICAL DATA**

Product code	Product description	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Volume	Gross weight
4058075106437	LED Switch Batten 8 W 3000 K	Shipping carton box 8	645 mm x 203 mm x 98 mm	12.83 dm <sup>3</sup>	2671.00 g

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

---

**DISCLAIMER**

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.