

# PRODUCT DATASHEET

## DULUX S LED EM 6 W/3000 K

OSRAM DULUX S LED EM | LED replacement for short CFLni, with 2-pin G23 base for CCG and AC mains operation



---

### AREAS OF APPLICATION

- General illumination within ambient temperatures from -20...+45 °C
- Supermarkets and department stores
- Walkways and corridors
- Hotels, restaurants

---

### PRODUCT BENEFITS

- Quick, simple and safe replacement without rewiring
- Low energy consumption
- Easy relamping thanks to compact design

---

### PRODUCT FEATURES

- LED replacement for conventional lamps for use in CCG luminaires
- Type of protection: IP20
- Lifetime: up to 30,000 h
- Single-ended two-pin plug-in G23 base



**TECHNICAL DATA**

Electrical data

<b>Rated wattage</b>	6.00 W
<b>Nominal wattage</b>	6.00 W
<b>Nominal voltage</b>	220...240 V
<b>Operating frequency</b>	50...60 Hz
<b>Power factor <math>\lambda</math></b>	> 0.50

Photometrical data

<b>Nominal luminous flux</b>	630 lm
<b>Rated luminous flux</b>	630 lm
<b>Rated color temperature</b>	3000 K
<b>Lumen main.fact.at end of nom.life time</b>	0.70
<b>Light color (designation)</b>	Warm White
<b>Color temperature</b>	3000 K
<b>Luminous flux</b>	630 lm
<b>Color rendering index Ra</b>	>80
<b>Standard deviation of color matching</b>	$\leq 6$ sdc <sub>m</sub>
<b>Color rendering index Ra</b>	>80

Light technical data

<b>Warm-up time (60 %)</b>	< 0.50 s
<b>Starting time</b>	< 0.5 s

Dimensions & weight



<b>Overall length</b>	237.0 mm
<b>Diameter</b>	33.0 mm
<b>Outer bulb</b>	-
<b>Length</b>	237.0 mm

## Temperatures &amp; operating conditions

Ambient temperature range	-20...+45 °C
Maximum temperature at tc test point	65 °C

## Lifespan

Nominal lamp life time	30000 h
Rated lamp life time	30000 h
Number of switching cycles	200000
Lumen maintenance at end of service life	0.70

## Additional product data

Base (standard designation)	G23
Mercury content	0.0 mg
Mercury-free	Yes
Design / version	Frosted
Show WEEE picto	Yes

## Capabilities

Dimmable	No
----------	----

## Certificates &amp; standards

Energy efficiency class	A+
Energy consumption	6 kWh/1000h

## Country-specific categorizations

Order reference	DULUX S11LED 6W
-----------------	-----------------

## SAFETY ADVICE

Not suitable for tandem operation.

## LOGISTICAL DATA

Product code	Product description	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Volume	Gross weight
4058075135321	DULUX S LED EM 6 W/3000 K	Shipping carton box 10	265 mm x 195 mm x 75 mm	3.88 dm <sup>3</sup>	732.00 g

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

## DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.