

PRODUCT DATASHEET

SMART+ SPOT GU10 4.5 W 220...240 V 36° GU10

SMART+ SPOT GU10 DIM | LED retrofit lamps with smart home technology, dimmable



AREAS OF APPLICATION

- General illumination
- Outdoor applications only in suitable luminaires

PRODUCT BENEFITS

- Up to 80 % less energy consumption compared to halogen lamps
- Easy to install and use
- Contains no mercury

PRODUCT FEATURES

- LED PAR 16 lamp with wireless smart lighting function
- Dimmable
- Network protocol: ZigBee 3.0
- Lifetime: up to 20,000 h
- Controllable via compatible smart home system (gateway and app) or SMART+ Switch
- For full functionality connection to a compatible smart home System (gateway and app) required



TECHNICAL DATA

Electrical data

| | |
|--|-------------|
| Operating frequency | 50...60 Hz |
| Rated wattage | 4.50 W |
| Power factor λ | > 0.50 |
| Nominal wattage | 4.50 W |
| Nominal voltage | 220...240 V |
| Claimed equiv. conventional lamp power | 50 W |


Photometrical data

| | |
|---|---------------------------|
| Light color (designation) | Warm White |
| Lumen main.fact.at end of nom.life time | 0.70 |
| Standard deviation of color matching | ≤ 6 sdc _m |
| Rated luminous flux | 350 lm |
| Nominal luminous flux | 350 lm |
| Rated color temperature | 2700 K |
| Color rendering index Ra | >80 |
| Nominal useful luminous flux 90° | 350 lm |
| Rated useful luminous flux 90° | 350 lm |
| Nom. useful luminous flux 120° | 350 lm |
| Rated useful luminous flux 120° | 350 lm |

Light technical data

| | |
|------------------------------------|----------|
| Beam angle | 36 ° |
| Starting time | < 0.5 s |
| Warm-up time (60 %) | < 0.50 s |
| Nominal beam angle | 36 ° |
| Rated beam angle (half peak value) | 36.00 ° |

Dimensions & weight



| | |
|-------------------------|---------|
| Product weight | 80.00 g |
| Outer bulb | PAR51 |
| Length | 55.0 mm |
| Diameter | 50.0 mm |
| Overall length | 55.0 mm |
| Maximum diameter | 50.0 mm |

Lifespan

| | |
|---|---------|
| Number of switching cycles | 100000 |
| Rated lamp life time | 20000 h |
| Nominal lamp life time | 20000 h |
| Lumen maintenance at end of service life | 0.70 |

Additional product data

| | |
|------------------------------------|--|
| Mercury-free | Yes |
| Show WEEE picto | Yes |
| Product remark | All technical parameters apply to the entire lamp/Due to the complex production process for light-emitting diodes, the typical values shown for the technical LED parameters are purely statistical values that do not necessarily match the actual technical parameters of each individual product, which can vary from the typical value |
| Base (standard designation) | GU10 |

Capabilities

| | |
|-----------------|-----|
| Dimmable | Yes |
|-----------------|-----|

Certificates & standards

| | |
|--------------------------------|-------------|
| Energy efficiency class | A+ |
| Energy consumption | 5 kWh/1000h |

EQUIPMENT / ACCESSORIES

- Control via app requires LIGHTIFY system (app and gateway) or other compatible Smart home system

LOGISTICAL DATA

| Product code | Product description | Packaging unit (Pieces/Unit) | Dimensions (length x width x height) | Volume | Gross weight |
|---------------|---|---------------------------------|---|----------------------|--------------|
| 4058075148338 | SMART+ SPOT GU10 4.5 W 220...240 V 36° GU10 | Shipping carton box 4 | 173 mm x 108 mm x 141 mm | 2.63 dm ³ | 577.00 g |

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.