

PRODUCT DATASHEET

P HQL LED 6000 lm 46 W/830 E40

HQL LED | Special LED lamps



AREAS OF APPLICATION

- Streets
- Area lighting
- Pedestrian zones
- Parks
- Industry
- Outdoor applications only in suitable luminaires

PRODUCT BENEFITS

- Saves up to 78 % energy when used as replacement for mercury vapor lamps (HQL)
- Effective thermal management for wide operating temperature range
- Low maintenance costs thanks to long lifetime
- Instant 100 % light, no warm-up time

PRODUCT FEATURES

- LED alternative for applications requiring a high luminous flux
- Integrated ECG with high power factor
- Type of protection: IP65
- High surge protection: up to 4 kV (L-N)
- Suitable for operation with conventional control gear or line voltage



TECHNICAL DATA

Electrical data

Rated wattage	46.00 W
Nominal wattage	46.00 W
Nominal voltage	220...240 V
Operating frequency	50...60 Hz
Power factor λ	> 0.90


Photometrical data

Nominal luminous flux	6000 lm
Rated luminous flux	6000 lm
Rated color temperature	3000 K
Color rendering index Ra	≥ 80
Lumen main.fact.at end of nom.life time	0.70
Light color (designation)	Warm White
Standard deviation of color matching	≤ 6 sdcn

Light technical data

Warm-up time (60 %)	< 0.50 s
Starting time	< 0.5 s

Dimensions & weight



Overall length	210.0 mm
Diameter	80.0 mm
Outer bulb	-
Product weight	700.00 g
Length	210.0 mm

Temperatures & operating conditions

Ambient temperature range	-20...+60 °C
----------------------------------	--------------

Lifespan

Nominal lamp life time	50000 h
Rated lamp life time	50000 h
Number of switching cycles	100000
Lumen maintenance at end of service life	0.70

Additional product data

Base (standard designation)	E40
Mercury content	0.0 mg
Mercury-free	Yes
Design / version	Clear
Show WEEE picto	Yes

Capabilities

Dimmable	No
-----------------	----

Certificates & standards

Type of protection	IP65
Energy efficiency class	A++
Energy consumption	46 kWh/1000h

Country specific categorizations

Order reference	HQLLED6000 46W/
------------------------	-----------------

LOGISTICAL DATA

Product code	Product description	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Volume	Gross weight
4058075037380	P HQL LED 6000 lm 46 W/830 E40	Shipping carton box 6	304 mm x 256 mm x 206 mm	16.03 dm ³	5883.00 g

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.