

# PRODUCT DATASHEET

## ST8A-EM 14 W/865 1200 mm

SubstiTUBE Advanced | High performance LED tubes for electromagnetic control gears



---

### AREAS OF APPLICATION

- General illumination within ambient temperatures from -20...+50 °C
- Illumination of production areas
- Traffic zones and corridors
- Supermarkets and department stores
- Industry

---

### PRODUCT BENEFITS

- Quick, simple and safe replacement without rewiring
- Energy savings of up to 60 % (compared to T8 fluorescent lamp on CCG)
- Instant-on light, therefore ideally suitable in combination with sensor technology
- Very high resistance to switching loads
- Also suitable for operation at low temperatures

---

### PRODUCT FEATURES

- LED alternative to classic T8 fluorescent lamps in CCG luminaires
- Bright, robust and durable
- Uniform illumination
- Single and tandem operation on conventional control gear (0.6 m version)
- Tube made of glass
- Mercury-free and RoHS compliant
- Type of protection: IP20



- Integrated ECG with high power factor

**TECHNICAL DATA**

Electrical data

Nominal wattage	14.00 W
Rated wattage	14.00 W
Nominal voltage	220...240 V
Operating frequency	50...60 Hz
Nominal current	0.065 A
Type of current	AC
Power factor $\lambda$	> 0.90


Photometrical data

Light color (designation)	Cool Daylight
Rated color temperature	6500 K
Nominal luminous flux	2100 lm
Rated luminous flux	2100 lm
Color rendering index Ra	>80
Lumen main.fact.at end of nom.life time	0.70
Standard deviation of color matching	$\leq 4$ sdcn

Light technical data

Starting time	< 0.5 s
Warm-up time (60 %)	< 0.50 s
Rated beam angle (half peak value)	160.00 °

Dimensions & weight



Length with base excl. base pins/connection	1200.00 mm
Product weight	198.00 g
Overall length	1213 mm

## Temperatures &amp; operating conditions

<b>Ambient temperature range</b>	-20...+50 °C
----------------------------------	--------------

## Lifespan

<b>Lifespan</b>	50000 h
<b>Nominal lamp life time</b>	50000 h
<b>Rated lamp life time</b>	50000 h
<b>Number of switching cycles</b>	200000

## Additional product data

<b>Base (standard designation)</b>	G13
<b>Mercury-free</b>	Yes

## Capabilities

<b>Dimmable</b>	No
-----------------	----

## Certificates &amp; standards

<b>Type of protection</b>	IP20
<b>Standards</b>	CE; VDE
<b>Energy efficiency class</b>	A++
<b>Energy consumption</b>	14 kWh/1000h

## Country specific categorizations

<b>ILCOS</b>	DR-14/865-G13-25.5/1213
<b>Order reference</b>	ST8A-1.2M 14W/8

## Logistical data

<b>Temperature range at storage</b>	-20...80 °C
-------------------------------------	-------------

## EQUIPMENT / ACCESSORIES

- Suitable for operation with low-loss and conventional control gears

## SAFETY ADVICE

Not suitable for operation with electronic control gear.

Operation in outdoor applications in suitable damp-proof luminaires possible according to data sheet and installation instruction.

## LOGISTICAL DATA

Product code	Product description	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Volume	Gross weight
4058075818156	ST8A-EM 14 W/865 1200 mm	Shipping carton box 10	1352 mm x 210 mm x 115 mm	32.65 dm <sup>3</sup>	3150.00 g

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

---

#### REFERENCES / LINKS

For current information see

▶ [www.ledvance.com/substitute](http://www.ledvance.com/substitute)

---

#### LEGAL ADVICE

When used to replace a T8 fluorescent lamp the total energy efficiency and light distribution depends on the design of the lighting system.

---

#### DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.