

# PRODUCT DATASHEET

## P RF R63 19 60° 2.8 W/2700 K E27

PARATHOM Retrofit R63 | LED reflector lamps R63 with retrofit screw base



---

### AREAS OF APPLICATION

- Domestic applications
- General illumination
- Outdoor applications only in suitable luminaires
- Perfect for decorative installations

---

### PRODUCT BENEFITS

- Replacement for white halogen reflector lamps up to 40 W
- Very low energy consumption
- Long lifetime of up to 15,000 h
- Clear lamps with innovative LED "filament" technology
- Design, dimensions, luminous flux comparable to an incandescent or halogen lamp

---

### PRODUCT FEATURES

- Professional LED lamps for line voltage
- Not dimmable
- Base: E27
- Mercury-free lamps



## TECHNICAL DATA

### Electrical data

Rated wattage	2.80 W
Nominal wattage	2.80 W
Nominal voltage	220...240 V
Claimed equiv. conventional lamp power	19 W
Operating frequency	50...60 Hz
Power factor $\lambda$	> 0.40


### Photometrical data

Luminous intensity [PIM]	300 cd
Nominal luminous flux	180 lm
Rated luminous flux	180 lm
Rated color temperature	2700 K
Lumen main.fact.at end of nom.life time	0.70
Light color (designation)	Warm White
Color temperature	2700 K
Luminous flux	180 lm
Color rendering index Ra	$\geq 80$
Standard deviation of color matching	$\leq 6$ sdc
Color rendering index Ra	$\geq 80$
Nominal useful luminous flux 90°	180 lm
Rated useful luminous flux 90°	180 lm

### Light technical data

Beam angle	60 °
Warm-up time (60 %)	< 0.50 s
Starting time	< 0.5 s
Nominal beam angle	60 °
Rated beam angle (half peak value)	60.00 °

Dimensions & weight



<b>Overall length</b>	104.0 mm
<b>Diameter</b>	63.0 mm
<b>Outer bulb</b>	R63
<b>Length</b>	104.0 mm
<b>Maximum diameter</b>	63.0 mm

Temperatures & operating conditions

<b>Maximum temperature at tc test point</b>	45 °C
---	-------

Lifespan

<b>Nominal lamp life time</b>	15000 h
<b>Rated lamp life time</b>	15000 h
<b>Number of switching cycles</b>	100000

Additional product data

<b>Base (standard designation)</b>	E27
<b>Mercury content</b>	0.0 mg
<b>Mercury-free</b>	Yes
<b>Design / version</b>	Clear
<b>Show WEEE picto</b>	Yes
<b>Product remark</b>	All technical parameters apply to the entire lamp/Due to the complex production process for light-emitting diodes, the typical values shown for the technical LED parameters are purely statistical values that do not necessarily match the actual technical parameters of each individual product, which can vary from the typical value

Capabilities

<b>Dimmable</b>	No
-----------------	----

Certificates & standards

Energy efficiency class	A+
Energy efficiency class	A+
Energy consumption	3 kWh/1000h

## Country-specific categorizations

ILCOS	DRRR-5/827-220-240-E27-63/50
Order reference	LEDPR6319 2,8W/

## LOGISTICAL DATA

Product code	Product description	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Volume	Gross weight
4052899972735	P RF R63 19 60° 2.8 W/2700 K E27	Shipping carton box 10	342 mm x 142 mm x 123 mm	5.97 dm <sup>3</sup>	593.00 g

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

## REFERENCES / LINKS

For further products and actual information concerning LED lamps see

▶ [www.ledvance.com/ledlamps](http://www.ledvance.com/ledlamps)

For Guarantee see

▶ [www.ledvance.com/guarantee](http://www.ledvance.com/guarantee)

## DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.