

PRODUCT DATASHEETDULUX D LED EM 7 W/6500 K

OSRAM DULUX D LED EM | LED replacement for conventional compact fluorescent lamps without integrated control gear



AREAS OF APPLICATION

- General illumination within ambient temperatures from 20...+35 $^{\circ}\text{C}$
- Supermarkets and department stores
- Walkways and corridors
- Hotels, restaurants

PRODUCT BENEFITS

- Quick, simple and safe replacement without rewiring
- Low energy consumption
- Easy relamping thanks to compact design

PRODUCT FEATURES

- LED replacement for conventional lamps for use in CCG luminaires
- Type of protection: IP20
- Lifetime: up to 30,000 h
- Single-ended two-pin plug-in G24d base



TECHNICAL DATA

Electrical data

Rated wattage	7.00 W
Nominal wattage	7.00 W
Nominal voltage	220240 V
Operating frequency	5060 Hz
Power factor λ	> 0.90

Photometrical data

Nominal luminous flux	700 lm		
Rated luminous flux	700 lm		
Rated color temperature	6500 K		
Lumen main.fact.at end of nom.life time	0.70		
Light color (designation)	Cool Daylight		
Color temperature	6500 K		
Luminous flux	700 lm		
Color rendering index Ra	>83		
Standard deviation of color matching	≤6 sdcm		
Color rendering index Ra	>83		

Light technical data

Warm-up time (60 %)	< 0.50 s	
Starting time	< 0.5 s	

Dimensions & weight



Overall length	147.5 mm
Diameter	34.5 mm
Outer bulb	-
Length	147.5 mm

Temperatures & operating conditions

Maximum temperature at tc test point	80 °C

Lifespan

Nominal lamp life time	30000 h
Rated lamp life time	30000 h
Number of switching cycles	200000
Lumen maintenance at end of service life	0.70

Additional product data

Base (standard designation)	G24d-2
Mercury content	0.0 mg
Mercury-free	Yes
Design / version	Frosted
Show WEEE picto	Yes

Capabilities

Dimmable	No
----------	----

Certificates & standards

Energy efficiency class	A+	
Energy efficiency class	A+	
Energy consumption	8 kWh/1000h	

Country-specific categorizations

Order reference	DULUX D LED 7W/

SAFETY ADVICE

Do not use with closed luminaire

LOGISTICAL DATA

Product code	Product description	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Volume	Gross weight
4058075024953	DULUX D LED EM 7 W/6500 K	Shipping carton box 10	205 mm x 91 mm x 180 mm	3.36 dm ³	842.00 g

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.