

# PRODUCT DATASHEET

## SILARA 410 22 W 827-860 Remote-CCT

SILARA | LED ceiling luminaires, dimmable



---

### AREAS OF APPLICATION

- For indoor use only
- Decorative domestic lighting
- Ceiling and wall surface mounting

---

### PRODUCT BENEFITS

- Very homogenous light
- Easy and quick installation

---

### PRODUCT FEATURES

- Ceiling luminaire with advanced LED technology
- Circular light emission



**TECHNICAL DATA**


Electrical data

<b>Nominal wattage</b>	21.50 W
<b>Operating mode</b>	Mains voltage
<b>Nominal voltage</b>	220...240 V
<b>Mains frequency</b>	50/60 Hz

Photometrical data

<b>Color temperature</b>	3000 K
<b>Color rendering index Ra</b>	>80
<b>Light color (designation)</b>	Warm White/Cool Daylight
<b>Luminous flux</b>	1400 lm

Dimensions & weight



<b>Diameter</b>	410.0 mm
<b>Height</b>	88.0 mm
<b>Product weight</b>	920.00 g

Colors & materials

<b>Body material</b>	Polycarbonate (PC)
<b>Housing color</b>	White
<b>Product color</b>	White

Lifespan

<b>Lifespan</b>	25000 h
-----------------	---------

Additional product data

<b>Mounting type</b>	Surface
<b>Mounting location</b>	Ceiling

## Capabilities

<b>Dimmable</b>	Yes
<b>Type of connection</b>	Terminal, 3-Pole (L, N, PE)

## Certificates &amp; standards

<b>Protection class</b>	I
<b>Type of protection</b>	IP20
<b>Standards</b>	CE/REACH/RoHS

## EQUIPMENT / ACCESSORIES

- Complete mounting and connecting accessories included

## LOGISTICAL DATA

Product code	Product description	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Volume	Gross weight
4058075032996	SILARA 410 22 W 827-860 Remote-CCT	Shipping carton box 6	652 mm x 472 mm x 450 mm	138.48 dm <sup>3</sup>	11162.00 g

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

## DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.