

Product datasheet

ST8V-EM 7.6 W/840 600 mm

SubstiTUBE Value | Economic LED tubes for electromagnetic control gears



- General illumination within ambient temperatures from -20...+45 °C Corridors, stairways, parking garages Industry Warehouses Cooling and storage rooms Warehouses Domestic applications Supermarkets and department stores

- No bending thanks to glass tube Energy savings of up to 68 % (compared to T8 fluorescent lamp on CCG) Quick, simple and safe replacement without rewiring Instant-on light, therefore ideally suitable in combination with sensor technology Very high resistance to switching loads Also suitable for operation at low temperatures



Product datasheet

Technical data

Electrical data

Max. lamp no. on circuit break. 10 A (B)	210
Max. lamp no. on circuit break. 16 A (B)	340
Rated wattage	7.60 W
Operating frequency	50...60 Hz
Power factor λ	> 0.90
Nominal wattage	7.60 W
Nominal voltage	220...240 V
Nominal current	0.037 A
Claimed equiv. conventional lamp power	18 W

Photometrical data

Standard deviation of color matching	≤ 6 sdc _m
Rated luminous flux	800 lm
Nominal luminous flux	800 lm
Rated color temperature	4000 K
Color rendering index Ra	>80
Color temperature	4000 K
Light color (designation)	Cool White
Luminous flux	800 lm
Lumen main.fact.at end of nom.life time	0.70

Light technical data

Warm-up time (60 %)	< 0.50 s
Beam angle	170 °
Starting time	< 0.5 s

Product datasheet

Dimensions & weight



Product weight	103.00 g
Length	602.0 mm
Outer bulb	T8
Overall length	602.0 mm
Diameter	25.6 mm

Temperatures & operating conditions

Temperature range at storage	-20...80 °C
Ambient temperature range	-20...+45 °C

Lifespan

Nominal lamp life time	30000 h
Rated lamp life time	30000 h
Lumen maintenance at end of service life	0.70
Number of switching cycles	200000

Additional product data

Appropriate disposal acc. to WEEE	Yes
Successor EAN	4058075454460
Mercury content	0.0 mg
Mercury-free	Yes
Base (standard designation)	G13

Capabilities

Dimmable	No
----------	----

Certificates & standards

Product datasheet

Energy efficiency class	A+
Energy consumption	8 kWh/1000h
Type of protection	IP20

Country specific categorizations

Order reference	ST8V-0.6M 7,6W/
-----------------	-----------------

Environmental information

Information according Art. 33 of EU Regulation (EC) 1907/2006 (REACH)	
Date of Declaration	18-04-2022
Primary Article Identifier	4058075024632
Declaration No. in SCIP database	In work

Equipment / Accessories

- Suitable for operation with low-loss and conventional control gears

Ecodesign regulation information:

Separate control gear and light sources must be disposed of at certified disposal companies in accordance with Directive 2012/19/EU (WEEE) in the EU and with Waste Electrical and Electronic Equipment (WEEE) Regulations 2013 in the UK. For this purpose, collection points for recycling centres and take-back systems (CRSO) are available from retailers or private disposal companies, which accept separate control gear and light sources free of charge. In this way, raw materials are conserved and materials are recycled.

Logistical Data

Product code	Product description	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Volume	Gross weight
4058075024632	ST8V-EM 7.6 W/840 600 mm	Shipping carton box 10 Pieces Sleeves	668 mm x 154 mm x 65 mm	6.69 dm ³	823.00 g
4058075024632	ST8V-EM 7.6 W/840 600 mm	Shipping carton box 10 Pieces Sleeves	742 mm x 210 mm x 115 mm	17.92 dm ³	1652.00 g

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

References / Links

For current information see

- ▶ www.osram.com/substitute

Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.

OSRAM is distribution partner
of LEDVANCE of LAMPS

OSRAM

OSRAM GmbH
Marcel-Breuer-Strasse 6
80807 Munich, Germany