

PRODUCT DATASHEET

ST CLAS P 25 2.5 W/2700K E14

BELLALUX CLP | LED lamps, classic mini-ball shape



AREAS OF APPLICATION

- General illumination
- Domestic applications
- Outdoor use in outdoor luminaires only (minimum IP65)

PRODUCT BENEFITS

- Lower thermal output (compared with the standard reference product)
- Very low energy consumption
- Shockproof and vibration-proof thanks to LED technology
- No UV and near-IR radiation in the light beam
- Instant 100 % light, no warm-up time
- Simple direct replacement for conventional incandescent lamps

PRODUCT FEATURES

- LED lamps for line voltage
- Not suitable for use with dimmers
- Mercury-free lamps



TECHNICAL DATA

Electrical data

Nominal wattage	2.50 W
Operating frequency	50...60 Hz
Rated wattage	2.50 W
Power factor λ	> 0.50
Nominal voltage	220...240 V
Claimed equiv. conventional lamp power	25 W
Max. lamp no. on circuit break. 10 A (B)	263
Max. lamp no. on circuit break. 16 A (B)	421


Photometrical data

Light color (designation)	Warm White
Color temperature	2700 K
Luminous flux	250 lm
Color rendering index Ra	≥ 80
Lumen main.fact.at end of nom.life time	0.70
Standard deviation of color matching	≤ 6 sdcn
Rated luminous flux	250 lm
Nominal luminous flux	250 lm
Rated color temperature	2700 K
Color rendering index Ra	≥ 80

Light technical data

Starting time	< 0.5 s
Warm-up time (60 %)	< 0.50 s

Dimensions & weight



Outer bulb	P45
------------	-----

Length	77.0 mm
Diameter	45.0 mm
Overall length	77.0 mm

Temperatures & operating conditions

Maximum temperature at tc test point	56 °C
Ambient temperature range	-20...+40 °C

Lifespan

Number of switching cycles	100000
Rated lamp life time	15000 h
Nominal lamp life time	15000 h
Lumen maintenance at end of service life	0.70

Additional product data

Base (standard designation)	E14
Design / version	Frosted
Mercury-free	Yes
Show WEEE picto	Yes
Product remark	All technical parameters apply to the entire lamp/Due to the complex production process for light-emitting diodes, the typical values shown for the technical LED parameters are purely statistical values that do not necessarily match the actual technical parameters of each individual product, which can vary from the typical value
Mercury content	0.0 mg

Capabilities

Dimmable	No
-----------------	----

Certificates & standards

Energy efficiency class	A++
Energy consumption	3 kWh/1000h

LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4058075115293	Folding carton box 1	46 mm x 61 mm x 94 mm	25.00 g	0.26 dm ³
4058075115309	Shipping carton box 10	252 mm x 134 mm x 104 mm	323.00 g	3.51 dm ³
4058075302785	Blister 1	45 mm x 140 mm x 120 mm	26.00 g	0.76 dm ³

4058075302792	Shipping carton box 6	285 mm x 153 mm x 136 mm	292.00 g	5.93 dm ³
---------------	--------------------------	--------------------------	----------	----------------------

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.