

PRODUCT DATASHEETP CLAS A 75 9.5 W/2700 K E27

PARATHOM CLASSIC A FACILITY | Professional LED Lamps with added function



AREAS OF APPLICATION

- Wherever light is required quickly
- Hotels, restaurants
- Outdoor applications only in suitable luminaires

PRODUCT BENEFITS

- Light also during power outages thanks to backup battery
- Very long lifetime of up to 25,000 h
- Instant 100 % light, no warm-up time
- Variable use at Direct Current, Alternating Current or battery voltage

PRODUCT FEATURES

- Operating time on battery power: up to 2 h (100 lm)
- Battery charging time: 4 h
- Battery technology: lithium-ion
- Battery charges while the lamp is powered by the mains
- Battery integrated and not interchangeable



TECHNICAL DATA


Electrical data

| Rated wattage | 9.50 W |
|---------------------|----------|
| Nominal wattage | 9.50 W |
| Nominal voltage | 220240 V |
| Operating frequency | 5060 Hz |

Photometrical data

| Rated color temperature | 2700 K |
|---|------------|
| Lumen main.fact.at end of nom.life time | 0.70 |
| Light color (designation) | Warm White |
| Color temperature | 2700 K |
| Luminous flux | 1055 lm |
| Color rendering index Ra | ≥80 |
| Nominal luminous flux | 1055 lm |

Dimensions & weight





| | Overall length | 142.0 mm |
|--|----------------|----------|
|--|----------------|----------|

Lifespan

| Nominal lamp life time | 25000 h |
|----------------------------|---------|
| Rated lamp life time | 25000 h |
| Number of switching cycles | 100000 |

Additional product data

| Base (standard designation) | E27 |
|-----------------------------|-----|
| Mercury-free | Yes |

| Product remark | All technical parameters apply to the entire lamp/Due to the complex production process for light-emitting diodes, the typical values shown for the technical LED parameters are purely statistical values that do not |
|----------------|--|
| | necessarily match the actual technical parameters of each individual product, which can vary from the typical value |

Capabilities

| Dimmable No | 0 |
|--------------------|---|
|--------------------|---|


Certificates & standards

| Energy efficiency class | A+ |
|-------------------------|----|
| | |

Country-specific categorizations

| Order reference | LEDPCLA75FA 9,5 |
|-----------------|-----------------|
| | |

Light Distribution



LDC typ polar

LOGISTICAL DATA

| Product code | Product description | Packaging unit (Pieces/Unit) | Dimensions (length x width x height) | Volume | Gross weight |
|---------------|---------------------------------|---------------------------------|--------------------------------------|----------------------|--------------|
| 4058075125889 | P CLAS A 75 9.5 W/2700 K E27 | Shipping carton box 10 | 315 mm x 131 mm x 126 mm | 5.20 dm ³ | 1133.00 g |

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.