

Product datasheetP RF CLAS A DIM 8 W/927 E27

PARATHOM Retrofit CLASSIC A DIM | Dimmable LED lamps, classic bulb shape



 Perfect for decorative installations Domestic applications General illumination Outdoor use in outdoor luminaires only (minimum IP65)

Design, dimensions, luminous flux comparable to an incandescent or halogen lamp Very low energy consumption Robust
against vibrations No UV and near-IR radiation in the light beam Instant 100 % light, no warm-up time No UV and near-IR
radiation in the light beam Can be easily fitted instead of ordinary light bulbs



Page 1 of 4

Product datasheet

Technical data

Electrical data

Rated wattage	8.00 W
Nominal wattage	8.00 W
Nominal voltage	220240 V
Operating frequency	5060 Hz
Max. lamp no. on circuit break. 10 A (B)	125
Max. lamp no. on circuit break. 16 A (B)	200
Nominal current	0.04 A
Claimed equiv. conventional lamp power	60 W


Photometrical data

Nominal luminous flux	806 lm
Rated luminous flux	806 lm
Rated color temperature	2700 K
Color rendering index Ra	95
Light color (designation)	Warm White
Standard deviation of color matching	≤6 sdcm
Color temperature	2700 K
Luminous flux	806 lm
Lumen main.fact.at end of nom.life time	0.70

Light technical data

Beam angle	300.00 °
Starting time	< 0.5 s

Dimensions & weight



Overall length	112.0 mm
----------------	----------

Product datasheet

Diameter	67.0 mm
Outer bulb	A67
Product weight	30.00 g
Length	112.0 mm

Temperatures & operating conditions

Ambient temperature range	-20+40 °C

Lifespan

Nominal lamp life time	15000 h
Rated lamp life time	15000 h
Number of switching cycles	100000
Lumen maintenance at end of service life	0.70

Additional product data

Base (standard designation)	E27
Mercury content	0.0 mg
Mercury-free	Yes
Appropriate disposal acc. to WEEE	Yes
Product remark	All technical parameters apply to the entire lamp/Due to the complex production process for light-emitting diodes, the typical values shown for the technical LED parameters are purely statistical values that do not necessarily match the actual technical parameters of each individual product, which can vary from the typical value/LED lamps contain several electronic components. Under unfavourable conditions these can lead to acoustic noise. In case of resonance even low noise can cause audible effect. Possible factors influencing this are the installation, the design of the lamp holder and the luminaire (acoustic resonance effect) as well as the dimmer or the transformer (harmonics or electronic resonance)

Capabilities

Primitable 103

Certificates & standards

Energy efficiency class	A+
Energy consumption	8 kWh/1000h
Type of protection	IP20

Country specific categorizations

Product datasheet

Order reference	LEDPCLA60D 8W/9

Environmental information

Information according Art. 33 of EU Regulation (EC) 1907/2006 (REACh)	
Date of Declaration	18-04-2022
Primary Article Identifier	4058075134485
Declaration No. in SCIP database	In work

Ecodesign regulation information:

Separate control gear and light sources must be disposed of at certified disposal companies in accordance with Directive 2012/19/EU (WEEE) in the EU and with Waste Electrical and Electronic Equipment (WEEE) Regulations 2013 in the UK. For this purpose, collection points for recycling centres and take-back systems (CRSO) are available from retailers or private disposal companies, which accept separate control gear and light sources free of charge. In this way, raw materials are conserved and materials are recycled.

Logistical Data

Product code	Product description	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Volume	Gross weight
4058075134485	P RF CLAS A DIM 8 W/927 E27	Shipping carton box 10 Pieces Folding carton box	348 mm x 145 mm x 159 mm	8.02 dm ³	677.00 g

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.

OSRAM is distribution partner of LEDVANCE of LAMPS



OSRAM GmbH Marcel-Breuer-Strasse 6 80807 Munich, Germany