

TOLEDO DECO BALL HOMELIGHT B22 SL

Item No: 0027522

SYLVANIA



- Compact design
- Ideal for festoon and decorative lighting
- Instant light at the flick of a switch
- Available in seven different colours - red, green, blue, frosted (2700K and 4000K), yellow and orange
- Suitable for replacement of incandescent and halogen coloured lamps
- Uniform light distribution
- Suitable for outdoor use in IP44 or IP65 rated festoon lighting strips
- Lower maintenance costs
- 15,000 hours average rated life

Technical Assets

Photometrics

General data

Product name	TOLEDO DECO BALL HOMELIGHT B22 SL
Technology	LED
Watt (Rated) (W)	1
Cap/Base	B22
Fixture rating	Open
General application	Residential & Consumer
Performance ambient temperature Tq (°C)	25
ETIM Class	EC001959
Warranty	3 years

Optical data

Useful luminous flux (Φ_{use})	70
Luminous flux (Rated) (lm)	70
Correlated colour temperature (k)	2700
Light colour	Homelight
CRI (Ra)	80
Lumen maintenance at end of nominal life (%)	70

Electrical data

Power consumption (W)	1
Wattage (W)	1
Starting time (max) (s)	0.5
Warm-up time to 60% of full light (max) (s)	1
Lamp power factor	0.2
No. Of switching cycles before premature failures	>50000
Nominal Frequency (Hz)	50/60Hz

Lifetime data

Average life (Nominal) (h)	15000
Average life (Rated) (h)	15000

Physical data

Nominal Product Length (mm)	67
Nominal Product Diameter (mm)	45
Weight (kg)	0.04

TOLEDO DECO BALL HOMELIGHT B22 SL

Item No: 0027522



Packaging

Product EAN number	5410288275222
Packaging single length / height (cm)	8.5
Packaging single width (cm)	4.5
Packaging single depth (cm)	4.5
DUN14 (inner)	15410288275229
Units per inner package	10
Packaging inner length / height (cm)	24.0
Packaging inner width (cm)	9.5
Packaging inner depth (cm)	9.0
Units per outer package	100
Packaging outer length / height (cm)	49.5
Packaging outer width (cm)	25.0

Safety data

Breakage cleaning instructions	Not applicable
Special purpose lamp	No
Dry applications use only	Yes
Suitable for household illumination	Yes
Safety message	Suitable for outdoor (in IP44)