ToLEDo Retro G9 ST 400LM 827 SL

Item No: 0029672
















LED retrofit replacement for halogen G9 mains voltage capsules ToLEDo Retro G9 has the same look and feel as halogen design thanks to glass construction body and wide light distribution Compact design Satin finish Omnidirectional light distribution 400lm = 35W halogen G9 lamp 90% energy saving Non-dimmable Suitable for chandeliers, interior display, shop windows, decorative and general lighting applications

Technical Assets

Dimensions (mm)



Photometrics

ToLEDo Retro G9 ST 400LM 827 SL

Item No: 0029672



General data

| Product name | ToLEDo Retro G9 ST 400LM 827 SL |
|-----------------------------------------|----------------------------------------|
| Technology | LED |
| Watt (Rated) (W) | 4.2 |
| Cap/Base | G9 |
| Fixture rating | Open |
| General application | Hospitality, Residential & Consumer |
| Operating temperature range (°C) | -20°C+45°C |
| Performance ambient temperature Tq (°C) | 25 |
| ETIM Class | EC001959 |
| E-number Fl | 4741144 |
| Warranty | 3 years |

Optical data

| opulai aata | |
|----------------------------------------------|-----------|
| Useful luminous flux (Φuse) | 400 |
| Luminous flux (Rated) (lm) | 400 |
| Correlated colour temperature (k) | 2700 |
| Light colour | Homelight |
| CRI (Ra) | 80 |
| Colour Variation Initial (SDCM) | SDCM6 |
| Photobiological Risk Group | RG1 |
| Lumen maintenance at end of nominal life (%) | 70 |

Electrical data

| Power consumption (W) | 4.2 |
|---------------------------------------------------|---------|
| Wattage (W) | 4.2 |
| Equivalent watt (W) | 35 |
| Primary Supply/Product voltage - min (V) | 220 |
| Primary Supply/Product voltage - max (V) | 240 |
| Control gear required | No |
| No. Of switching cycles before premature failures | >50000 |
| Dimmable | No |
| Inrush Current (A) | 1.2 |
| Inrush Duration (µs) | 520 |
| Lamp Energy Label (class) | F |
| Nominal Frequency (Hz) | 50/60Hz |
| Max. products per 16A C Breaker | 133 |
| Max. products per 16A B Breaker | 66 |

Lifetime data

| Lifespan L70 B50 | 15000 |
|----------------------------|-------|
| Average life (Nominal) (h) | 15000 |
| Average life (Rated) (h) | 15000 |

Physical data

| Nominal Product Length (mm) | 55.5 |
|-------------------------------|-------|
| Nominal Product Diameter (mm) | 18 |
| Weight (kg) | 0.008 |

Packaging

| Product EAN number | 5410288296722 |
|---------------------------------------|----------------|
| Packaging single length / height (cm) | 6.1 |
| Packaging single width (cm) | 5.1 |
| Packaging single depth (cm) | 8.2 |
| DUN14 (inner) | 15410288296729 |
| Units per outer package | 6 |
| Packaging outer length / height (cm) | 19.1 |
| Packaging outer width (cm) | 11.3 |

ToLEDo Retro G9 ST 400LM 827 SL

Item No: 0029672 SYLVANIA

Safety data

| Optimal operating condition (°C) | -20-45 |
|-------------------------------------|--------------------------------------------|
| Breakage cleaning instructions | Not applicable |
| Special purpose lamp | No |
| Dry applications use only | Yes |
| Suitable for household illumination | Yes |
| Safety message | Not Suitable for totally enclosed fixtures |