

# Product datasheet

## 16.4 W/865 1200 mm

**SubstiTUBE Value | Economic LED tubes for electromagnetic control gears (CCG)**



- General illumination within ambient temperatures from -20...+45 °C Corridors, stairways, parking garages Industry Warehouses Cooling and storage rooms Warehouses Domestic applications Supermarkets and department stores

- No bending thanks to glass tube Energy savings of up to 68 % (compared to T8 fluorescent lamp on CCG) Quick, simple and safe replacement without rewiring Instant-on light, therefore ideally suitable in combination with sensor technology Very high resistance to switching loads Also suitable for operation at low temperatures



Product datasheet

Technical data

Electrical data

Operating frequency	50...60 Hz
Nominal current	75 mA
Claimed equiv. conventional lamp power	36 W

Photometrical data

Light color (designation)	Cool Daylight
Luminous flux	1800 lm

Light technical data

Beam angle	190 °
------------	-------

Dimensions & weight



Product weight	190.00 g
Overall length	1212.00 mm

Temperatures & operating conditions

Ambient temperature range	-20...+45 °C
---------------------------	--------------

Lifespan

Lumen maintenance at end of service life	0.7
--	-----

Additional product data

Appropriate disposal acc. to WEEE	Yes
Successor EAN	4058075611719
Mercury content	0.0 mg
Mercury-free	Yes

Product datasheet

Predecessor EAN	4058075454545, 4058075024717
-----------------	------------------------------

Certificates & standards

Energy efficiency class	E
Energy consumption	17.00 kWh/1000h

Environmental information

Information according Art. 33 of EU Regulation (EC) 1907/2006 (REACH)	
Date of Declaration	18-04-2022
Primary Article Identifier	4058075454545   4058075611719
Declaration No. in SCIP database	In work

Equipment / Accessories

- Suitable for operation with low-loss and conventional control gears

Ecodesign regulation information:

Separate control gear and light sources must be disposed of at certified disposal companies in accordance with Directive 2012/19/EU (WEEE) in the EU and with Waste Electrical and Electronic Equipment (WEEE) Regulations 2013 in the UK. For this purpose, collection points for recycling centres and take-back systems (CRSO) are available from retailers or private disposal companies, which accept separate control gear and light sources free of charge. In this way, raw materials are conserved and materials are recycled.

Logistical Data

Product code	Product description	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Volume	Gross weight
4058075611719	16.4 W/865 1200 mm	Shipping carton box 10 Pieces Sleeves	1290 mm x 210 mm x 105 mm	28.44 dm <sup>3</sup>	2796.00 g

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.

OSRAM is distribution partner  
of LEDVANCE of LAMPS

**OSRAM**

OSRAM GmbH  
Marcel-Breuer-Strasse 6  
80807 Munich, Germany