



**Quadro 2700K 25° 350mA CRI90 m.Scheibe  
LED Einbaustr. 8W eisengeb.m.Konv.dim**  
Article nr.: ALU53395UWWD

for indoor use, IP 20 · · housing: diecast aluminum, glass reflector, protective glass · housing color: iron brushed · 30° swivelling · beam angle: 25° · power: 8 W · light color: 2700 K · luminous flux: 670 lm · CRI: >90 · lifetime L70: >= 33.000 h · input: 350 mA DC · protection class III, MM · installation depth: 40 mm · ceiling cut-out: 68 mm · outer dimensions: 82 x 82 mm · energie efficiency class: A+ · including LED converter dimmable via tronic dimmer

## TECHNICAL DATA

Unit Code	pcs
BAR code	4012094533957
Housing colour	Eisen-gebürstet
Length	82.00 mm
Width	82.00 mm
Height	31.00 mm
Hole size	68 mm
Depth in ceiling	40.00 mm
LED colour	UWW ca. 2700 K
Lightoutput per fixture	670.00 lm





**Quadro 2700K 25° 350mA CRI90 m.Scheibe  
LED Einbaustr. 8W eisengeb.m.Konv.dim**  
Article nr.: ALU53395UWWD

**TECHNICAL DATA**

Lamp	Inklusive LED
IP rating	20
Power	8 W
Current mA	350 mA
Lamp base	ohne
Amount of LED	1
Material	Aluminium
Temperature range	-20 - 40
Energy efficiency class	A+
CRI	≥ 90





**Quadro 2700K 25° 350mA CRI90 m.Scheibe  
LED Einbaustr. 8W eisengeb.m.Konv.dim**  
Article nr.: ALU53395UWWD

## TECHNICAL DRAWING

