

PRODUCT DATASHEET P CLAS P 40 DIM 4.5 W/827 E14

PARATHOM Retrofit CLASSIC P DIM | Dimmable LED lamps, classic bulb shape



AREAS OF APPLICATION

- Domestic applications
- General illumination
- Outdoor applications only in suitable luminaires
- Perfect for decorative installations

PRODUCT BENEFITS

- Design, dimensions, luminous flux comparable to an incandescent lamp
- Very low energy consumption
- Robust against vibrations
- Clear lamps with innovative LED "filament" technology
- Instant 100 % light, no warm-up time
- Can be easily fitted instead of ordinary light bulbs

PRODUCT FEATURES

- Professional LED lamps for line voltage
- Dimmable (with many common dimmers, see also www.ledvance.com/dim)
- Mercury-free lamps
- Lifetime: up to 15,000 h
- Beam angle: up to 300°
- Energy efficiency class: A++



December 20, 2017, 01:04:56 P CLAS P 40 DIM 4.5 W/827 E14

TECHNICAL DATA

Electrical data

| Rated wattage | 4.50 W |
|----------------------------------------|----------|
| Nominal wattage | 4.50 W |
| Nominal voltage | 220240 V |
| Operating frequency | 5060 Hz |
| Power factor λ | > 0.70 |
| Claimed equiv. conventional lamp power | 40 W |


Photometrical data

| Nominal luminous flux | 470 lm |
|-----------------------------------------|------------|
| Rated luminous flux | 470 lm |
| Rated color temperature | 2700 К |
| Color rendering index Ra | ≥80 |
| Lumen main.fact.at end of nom.life time | 0.70 |
| Light color (designation) | Warm White |
| Standard deviation of color matching | ≤6 sdcm |

Light technical data

| Warm-up time (60 %) | < 0.50 s |
|---------------------|----------|
| Starting time | < 0.5 s |

Dimensions & weight



| Overall length | 110.0 mm |
|----------------|----------|
| Diameter | 45.0 mm |
| Outer bulb | P45 |
| Length | 110.0 mm |

Lifespan

PRODUCT DATASHEET

| Nominal lamp life time | 20000 h | |
|----------------------------|---------|--|
| Rated lamp life time | 20000 h | |
| Number of switching cycles | 100000 | |

Additional product data

| Base (standard designation) E14 | | | |
|---------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--|--|
| Mercury content | 0.0 mg | | |
| Mercury-free | Yes | | |
| Design / version | Clear | | |
| Show WEEE picto | Yes | | |
| Product remark | All technical parameters apply to the entire lamp/Due to the complex production process for light-emitting diodes, the typical values shown for the technical LED parameters are purely statistical values that do not necessarily match the actual technical parameters of each individual product, which can vary from the typical value/In preparation | | |

Capabilities

| Dimmable | Yes |
|----------|-----|
|----------|-----|

Certificates & standards

| Energy efficiency class | A++ |
|-------------------------|-------------|
| Energy consumption | 5 kWh/1000h |

Country specific categorizations

| ILCOS | DRBP/C-4,5/827-220/240-E14-45 | |
|-----------------|-------------------------------|--|
| Order reference | LEDPCLP40D 4,5W | |

LOGISTICAL DATA

| Product code | Product description | Packaging unit (Pieces/Unit) | Dimensions (length x width x height) | Volume | Gross weight |
|---------------|----------------------------------|---------------------------------|-----------------------------------------|----------------------|--------------|
| 4058075808904 | P CLAS P 40 DIM 4.5 W/827 E14 | Shipping carton box 10 | 240 mm x 101 mm x 127 mm | 3.08 dm ³ | 426.00 g |

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.