



PING BALL

Typology

Range of LED lamps with SMD technology and color bulb.

Features

Classic shapes for immediate retro-fit of incandescent lamps in any decorative applications and festoons.

The RGB version features a fading color loop, for pleasant coloring effects.

Material

Impact-resistant globe, extremely resistant: these lamps can "bounce" if they fall on the floor.

Applications

For indoor or outdoor use inside duly protected fittings or Catenaria.

Notes

Do not use with dimmer.

BASIC

200-240
Vac

Ra 80



25000 h
L70B50

IP20

B22

-25°C
+35°C




320°



Characteristic data

Power	0.5 W	Beam	320°	Dimmable	No	Input	200-240 Vac
Base	B22	IP	20	Flux	20 lm	PF	0,16
Tc	6000 K	Ra	80	LED Warranty	G2		

Dimensional characteristics



Ø	45 mm
H	69 mm
H Tolerance	± 3 mm

Lighting and photometric features

Beam opening	320°
Flux	20 lm
CCT nominal colour temperature	6000 K
Colour of the light	Cool light
Colour rendering index	80
Lifespan	25000 h
LED lifespan	L70B50
Trigger time	<0,2 s
Heating time up to 60% of full efficiency	Instant Full Light
Mercury	0 mg

Electrical characteristics

Rated power	0.5 W
Input voltage	200-240 Vac
Frequency	50 Hz
Dimmable	No
Power factor (PF)	0,16
Input current	0.15 A
Weighted energy consumption	1 kWh/1000h
Number of cycles	100000
Operating temperature	-25°C / +35°C
Operating position	360°

LED Warranty

G2	Up to 2 years (4000h/year) *4000h = 11h a day x 365 days. Without limitations on the duration of use for the first year, provided the observance of the installation conditions.
----	--

European Directives

2009/125/EC * Ecodesign
2011/65/EU * RoHS
2012/19/EU * RAEE
2014/30/EU * EMC
2014/35/EU * LVD
2015/863 * Amending RoHS
2017/1369 * Regulation for Energy Labelling
2019/2015 * Regulation for Energy Labelling
2019/2020 * Regulation for Ecodesign
2021/340 * Amending Reg. Energy Labelling
2021/341 * Amending Reg. Ecodesign

Product standards

CEI EN 55015:2020 (+A11:2020)
CEI EN 60968:2016
CEI EN 61000-3-2:2019 (+A1:2021)
CEI EN 61000-3-3:2014 (+EC1:2014/+EC2:2016/+A1:2021/+A2:2022)
CEI EN 61547:2010
CEI EN 62031:2021 (+A11:2022)
CEI EN 62471:2010
IEC/TR 62471-2:2009
CEI EN 62560:2013 (+A1:2017/+A11:2020)
CEI 34-141:2014

Logistics data

Item net weight	20 gr
Barcode single item	8011905836702
Number of pieces multiple pack	10
Barcode multiple pack	8011905781989
Minimum order quantity	10
Minimum packaging	10 / 10