

PARATHOM PAR16 35 36° 5 W/827

PARATHOM PAR16 | LED reflector lamps PAR16 with retrofit pin base



Areas of application

- Spotlighting for accents
- · Display cabinets and shop windows
- · Retail outlets and exhibition rooms
- · Spotlighting heat-sensitive objects such as food, plants, etc.
- Outdoor use in outdoor luminaires only (minimum IP65)
- Directional light sources
- Hospitality
- Shops

Product benefits

- Excellent price/performance ratio
- Very low energy consumption
- · Extremely long life
- Robust against vibrations
- · No UV and near-IR radiation in the light beam
- · Professional thermal management
- · Efficient generation of white light

Product features

- · Professional LED lamps for line voltage
- Not dimmable
- Color temperature: 2,700 K
- \cdot Good color rendering (R_a \geq 80) and color stability throughout the life of the lamp
- · Base: GU10
- · Lifetime: up to 15,000 h
- Mercury-free lamps
- · High color consistency







Technical data

Electrical data

Rated wattage	4.40 W
Nominal wattage	4.00 W
Nominal voltage	220 V
Claimed equiv. conventional lamp power	35 W
Operating frequency	5060 Hz
Power factor λ	> 0.80
Energy consumption	5 kWh/1000h


Photometrical data

Luminous intensity	600 cd
Nominal luminous flux	230 lm
Rated luminous flux	230 lm
Color temperature	2700 K
Color rendering index Ra	80
Lumen main.fact.at end of nom.life time	0.70
Light color as per EN 12464-1	Warm White
Standard deviation of color matching	≤6 sdcm
Nominal useful luminous flux 90°	230 lm
Rated useful luminous flux 90°	230 lm
Rated peak intensity	650 cd

Light technical data

Beam angle	36 °
Warm-up time (60 %)	< 0.50 s
Starting time	< 0.5 s
Nominal beam angle	36.00 °
Rated beam angle (half peak value)	36.00 °

Dimensions & weight



Product line drawing

Overall length	58.0 mm
Diameter	50.0 mm
Outer bulb	PAR51
Length	58.0 mm
Maximum diameter	50.0 mm


Colors & materials

Lamp mercury content	0.0 mg	
Mercury-free	Yes	

Lifespan

Nominal lamp life time	15000 h
Rated lamp life time	15000 h
Number of switching cycles	100000

Additional product data



Spectral power distribution

Base (standard designation)	GU10	
New article	NEW	
Appropriate disposal acc. to WEEE	Yes	
Footnote only for product	All technical parameters apply to the entire lamp/Due to the complex production process for light-emitting diodes, the typical values shown for the technical LED parameters are purely statistical values that do not necessarily match the actual technical parameters of each individual product, which can vary from the typical value	

Capabilities

Dimmable	No
----------	----

Certificates & standards

Country specific categorizations

ILCOS	DRPAR-4,5-100-240-GU10-50/36	
Order reference	SPAR163536 4W/8	

Country specific information

Product code	METEL-Code	SEG number	STK number	UK Org
4052899910379	-	8334322	4739155	-

Logistical Data

Product code	Product description	Packaging unit (Pieces/Unit)	Dimensions (height x width x length)	Volume	Gross weight
4052899159396	PARATHOM PAR16 35 36° 5 W/827	Folding carton box 1	- x - x -		
4052899159402	PARATHOM PAR16 35 36° 5 W/827	Shipping carton box 10	109 mm x 117 mm x 275 mm	3.51 dm ³	860.00 g
4052899910379	PARATHOM PAR16 35 36° 5 W/827	Folding carton box 1	62 mm x 52 mm x 52 mm	0.17 dm³	70.00 g
4052899910478	PARATHOM PAR16 35 36° 5 W/827	Shipping carton box 10	78 mm x 116 mm x 275 mm	2.49 dm³	769.00 g
4008321879820	PARATHOM PAR16 35 36° 5 W/827	Shipping carton box 80	- x - x -		
4052899030466	PARATHOM PAR16 35 36° 5 W/827	Shipping carton box 80	- x - x -		

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

References / Links

For further products and actual information concerning LED lamps see

www.osram.com/ledlamps

For Guarantee see

www.osram.com/guarantee

Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.