

PARATHOM MR16 20 36° 2.8 W/827 GU5.3

PARATHOM MR16 | Low-voltage LED reflector lamps MR16 with retrofit pin base



Areas of application

- As a downlight for marking walkways, doors, stairs, etc.
- Exhibitions, department stores
- Outdoor applications only in suitable luminaires
- Directional light sources
- Museums
- Hospitality
- Shops

Product benefits

- Very low energy consumption
- Extremely long life
- Robust against vibrations
- No UV and near-IR radiation in the light beam
- Efficient generation of white light
- Excellent price/performance ratio

Product features

- Professional LED lamp
- Not dimmable
- Base: GU5.3
- Good color rendering ($R_a \geq 80$) and color stability throughout the life of the lamp
- Lifetime: up to 15,000 h
- Mercury-free lamps



Technical data

Electrical data

| | |
|--|------------|
| Rated wattage | 2.80 W |
| Nominal wattage | 2.80 W |
| Nominal voltage | 12.0 V |
| Claimed equiv. conventional lamp power | 20 W |
| Operating frequency | 50...60 Hz |
| Power factor λ | > 0.60 |

Photometrical data


| | |
|--------------------------------------|---------------------------|
| Luminous intensity | 600 cd |
| Nominal luminous flux | 230 lm |
| Rated luminous flux | 230 lm |
| Color temperature | 2700 K |
| Color rendering index Ra | 80 |
| Light color (designation) | Warm White |
| Standard deviation of color matching | ≤ 5 sdc _m |
| Nominal useful luminous flux 90° | 230 lm |
| Rated useful luminous flux 90° | 230 lm |
| Rated peak intensity | 600 cd |

Light technical data

| | |
|------------------------------------|---------|
| Beam angle | 36 ° |
| Warm-up time (60 %) | 0.20 s |
| Starting time | 0.1 s |
| Nominal beam angle | 36 ° |
| Rated beam angle (half peak value) | 36.00 ° |

Product datasheet

Dimensions & weight



| | |
|------------------|---------|
| Overall length | 51.7 mm |
| Diameter | 49.8 mm |
| Outer bulb | MR51 |
| Length | 51.7 mm |
| Maximum diameter | 50.0 mm |

Lifespan

| | |
|---|---------|
| Nominal lamp life time | 15000 h |
| Rated lamp life time | 15000 h |
| Number of switching cycles | 100000 |
| Lumen main.fact.at end of nom.life time | 0.70 |

Additional product data

| | |
|-----------------------------------|--|
| Base (standard designation) | GU5.3 |
| Lamp mercury content | 0.0 mg |
| Mercury-free | Yes |
| Appropriate disposal acc. to WEEE | Yes |
| Product remark | All technical parameters apply to the entire lamp/Due to the complex production process for light-emitting diodes, the typical values shown for the technical LED parameters are purely statistical values that do not necessarily match the actual technical parameters of each individual product, which can vary from the typical value |

Capabilities

| | |
|----------|----|
| Dimmable | No |
|----------|----|

Certificates & standards

Product datasheet

| | |
|-------------------------|-------------|
| Energy efficiency class | A++ |
| Energy consumption | 3 kWh/1000h |

Country specific categorizations

| | |
|-----------------|-----------------|
| Order reference | PMR162036 2,8W/ |
|-----------------|-----------------|



Guarantee

Equipment / Accessories

- Equipped with high-power LEDs
- Suitable for many commercially available electronic or conventional transformers

Logistical Data

| Product code | Product description | Packaging unit (Pieces/Unit) | Dimensions (length x width x height) | Volume | Gross weight |
|---------------|--|------------------------------|--------------------------------------|----------------------|--------------|
| 4052899943582 | PARATHOM MR16 20 36° 2.8 W/827 GU5.3 | Shipping carton box 10 | 267 mm x 111 mm x 69 mm | 2.04 dm ³ | 375.00 g |

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

References / Links

For further products and actual information concerning LED lamps see

- ▶ www.osram.com/ledlamps

For Guarantee see

- ▶ www.osram.com/guarantee

Further information see

- ▶ www.osram.com/low-voltage-ledlamps

Product datasheet

Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.