

PARATHOM MR16 20 36° ADV 3.3 W/827 GU5.3

PARATHOM advanced MR16 | Dimmable low-voltage LED reflector lamps MR16 with retrofit pin base



Areas of application

- As a downlight for marking walkways, doors, stairs, etc.
- Exhibitions, department stores
- Outdoor applications only in suitable luminaires
- Directional light sources
- Museums
- Hospitality
- Shops

Product benefits

- Very low energy consumption
- Extremely long life
- Robust against vibrations
- No UV and near-IR radiation in the light beam
- Efficient generation of white light

Product features

- Professional LED lamp
- Dimmable (with many common dimmers, see also www.osram.com/dim)
- Base: GU5.3
- Lifetime: up to 35,000 h
- Mercury-free lamps
- High color consistency; SDCM: < 5 (PARATHOM PRO)





Product datasheet

Technical data

Electrical data

Rated wattage	3.30 W	
Nominal wattage	3.30 W	
Nominal voltage	12.0 V	
Claimed equiv. conventional lamp power	20 W	
Operating frequency	5060 Hz	
Power factor λ	> 0.70	


Photometrical data

Luminous intensity	600 cd	
Nominal luminous flux	230 lm	
Rated luminous flux	230 lm	
Color temperature	2700 K	
Color rendering index Ra	80	
Light color (designation)	Warm White	
Standard deviation of color matching	≤5 sdcm	
Nominal useful luminous flux 90°	230 lm	
Rated useful luminous flux 90°	230 lm	
Rated peak intensity	600 cd	

Light technical data

Beam angle	36 °	
Warm-up time (60 %)	0.20 s	
Starting time	0.1 s	
Nominal beam angle	36 °	
Rated beam angle (half peak value)	36.00 °	

Dimensions & weight



Overall length	51.7 mm
Diameter	49.8 mm
Outer bulb	MR51
Length	51.7 mm
Maximum diameter	50.0 mm

Lifespan

Nominal lamp life time	25000 h
Rated lamp life time	25000 h
Number of switching cycles	100000
Lumen main.fact.at end of nom.life time	0.70

Additional product data

Base (standard designation)	GU5.3	
Lamp mercury content	0.0 mg	
Mercury-free	Yes	
Appropriate disposal acc. to WEEE	Yes	
Product remark	All technical parameters apply to the entire lamp/Due to the complex production process for light-emitting diodes, the typical values shown for the technical LED parameters are purely statistical values that do not necessarily match the actual technical parameters of each individual product, which can vary from the typical value/LED lamps contain several electronic components. Under unfavourable conditions these can lead to acoustic noise. In case of resonance even low noise can cause audible effect. Possible factors influencing this are the installation, the design of the lamp holder and the luminaire (acoustic resonance effect) as well as the dimmer or the transformer (harmonics or electronic resonance)	

Product datasheet

Capabilities

Dimmable	Yes ¹⁾

 $^{^{1)}}$ With many common dimmers, see also www.osram.com/dim

Certificates & standards

Energy efficiency class	A+	
Energy consumption	4 kWh/1000h	

Country specific categorizations

ILCOS	DRR-3,3/827-12-GU5.3-50/36	
Order reference	PMR16D2036 3,3W	



Guarantee

Equipment / Accessories

- Equipped with high-power LEDs
- Suitable for many commercially available electronic or conventional transformers

Logistical Data

Product code	Product description	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Volume	Gross weight
4052899943681	PARATHOM MR16 20 36° ADV 3.3 W/827 GU5.3	Shipping carton box 10	267 mm x 111 mm x 69 mm	2.04 dm ³	397.00 g

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

References / Links

For dimming conformity see

Product datasheet

www.osram.com/DIM

For further products and actual information concerning LED lamps see

www.osram.com/ledlamps

For Guarantee see

www.osram.com/guarantee

Further information see

www.osram.com/low-voltage-ledlamps

Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.