

## LIGHTIFY CLASSIC B 40 TW FR

LIGHTIFY CLASSIC B TW | LED retrofit lamps with LIGHTIFY technology, color temperature adjustable, classic mini-candle shape



### Areas of application

- General illumination
- Hospitality

### Product benefits

- Controllable via LIGHTIFY Switch and smart devices (via Android and iOS)
- With the advantages of LIGHTIFY system
- Individually controllable
- Easy to install and use
- Up to 80 % less energy consumption compared with ordinary light bulbs
- Contains no mercury

### Product features

- LED Classic B lamp with integrated wireless smart lighting function
- Adjustable light color via Tunable White: Warm White to Daylight (2,700 K...6,500 K)
- Dimmable via LIGHTIFY
- Lifetime: up to 20,000 h
- Color rendering index  $R_a$ : 80...89
- Frosted outer bulb
- Base: E14



---

Technical data

**Electrical data**

|  |             |
|--|-------------|
| Rated wattage                          | 6.00 W      |
| Nominal wattage                        | 6.00 W      |
| Nominal voltage                        | 220...240 V |
| Operating frequency                    | 50...60 Hz  |
| Power factor $\lambda$                 | > 0.50      |
| Claimed equiv. conventional lamp power | 40 W        |

**Photometrical data**


|                                      |                           |
|--------------------------------------|---------------------------|
| Color temperature                    | 2700 K                    |
| Nominal luminous flux                | 470 lm                    |
| Rated luminous flux                  | 470 lm                    |
| Color rendering index Ra             | $\geq 80$                 |
| Standard deviation of color matching | $\leq 6$ sdc <sub>m</sub> |

**Light technical data**

|                     |          |
|---------------------|----------|
| Warm-up time (60 %) | < 0.50 s |
| Starting time       | < 0.5 s  |

**Dimensions & weight**

---



|                |          |
|----------------|----------|
| Overall length | 106.0 mm |
| Diameter       | 38.0 mm  |
| Outer bulb     | B40      |
| Product weight | 65.00 g  |
| Length         | 110.0 mm |

**Lifespan**

---

## Product datasheet

|   |         |
|---|---------|
| Nominal lamp life time                  | 20000 h |
| Rated lamp life time                    | 25000 h |
| Number of switching cycles              | 100000  |
| Lumen main.fact.at end of nom.life time | 0.70    |

### Additional product data

|                                   |  |
|-----------------------------------|--|
| Base (standard designation)       | E14  |
| Lamp mercury content              | 0.0 mg   |
| Mercury-free                      | Yes  |
| Appropriate disposal acc. to WEEE | Yes  |
| Product remark                    | All technical parameters apply to the entire lamp/Due to the complex production process for light-emitting diodes, the typical values shown for the technical LED parameters are purely statistical values that do not necessarily match the actual technical parameters of each individual product, which can vary from the typical value |

### Capabilities

|          |                   |
|----------|-------------------|
| Dimmable | Yes <sup>1)</sup> |
|----------|-------------------|

<sup>1)</sup> Via LIGHTIFY function

### Certificates & standards

|                         |             |
|-------------------------|-------------|
| Energy efficiency class | A+          |
| Energy consumption      | 6 kWh/1000h |

### Equipment / Accessories

- LIGHTIFY APP required
- LIGHTIFY Gateway required

### Logistical Data

| Product code  | Product description         | Packaging unit (Pieces/Unit) | Dimensions (length x width x height) | Volume               | Gross weight |
|---------------|-----------------------------|------------------------------|--------------------------------------|----------------------|--------------|
| 4052899947214 | LIGHTIFY CLASSIC B 40 TW FR | Shipping carton box<br>4     | 211 mm x 167 mm x<br>141 mm          | 4.97 dm <sup>3</sup> | 727.00 g     |

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

### Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.