

# P CLAS P ADV GLdim 40 6.5 W/827 E14

PARATHOM CLASSIC P ADVANCED GLOWdim | LED lamps with GLOWdim effect, classic miniball shape



#### Areas of application

- Hospitality
- Historical buildings
- Residential interiors
- Marine lighting
- Outdoor applications only in suitable luminaires

### Product benefits

- Provides an especially warm light when dimmed down
- Directly controllable via standard dimmer, no remote control required
- Can be easily combined with other GLOWdim products in one application
- Very long lifetime of up to 25,000 h
- Low energy consumption
- Easy relamping thanks to compact design

#### **Product features**

- LED alternative to conventional lamps
- Dimming changes light color from warm white (2,700 K) to extra warm white (2,000 K)
- Good quality of light; color rendering index  $R_a: \ge 80$  Dimmable (with many common dimmers, see also www.ledvance.com/dim)
- Mercury-free lamps



January 18, 2017, 22:02:23 P CLAS P ADV GLdim 40 6.5 W/827 E14

# Product datasheet

### Technical data


### **Electrical data**

Rated wattage	6.50 W	
Nominal wattage	6.50 W	
Nominal voltage	220240 V	
Claimed equiv. conventional lamp power	40 W	
Operating frequency	5060 Hz	

### Photometrical data

Color temperature	2700 К	
Color rendering index Ra	≥80	
Lumen main.fact.at end of nom.life time	0.70	
Light color (designation)	Warm White	
Nominal luminous flux	470 lm	

## Dimensions & weight



Overall length	82.0 mm
Lifespan	
Nominal lamp life time	25000 h
Rated lamp life time	25000 h
Number of switching cycles	100000

## Additional product data

Base (standard designation)	E14
Mercury-free	Yes

# Product datasheet

	All technical parameters apply to the entire lamp/Due to the complex production process for light-emitting diodes, the typical values shown for the technical LED parameters are purely statistical values that do not necessarily match the actual technical parameters of each individual product, which can vary from the typical value
--	--

### Capabilities

Dimmable	Yes

### **Country specific categorizations**

ILCOS	DRAP/F-6,5/827-220-240-E14-43	
Order reference	PCLP40GLDIM 6,5	

### Logistical Data

Product code	Product description	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Volume	Gross weight
4052899960275	P CLAS P ADV GLdim 40 6.5 W/827 E14	Shipping carton box 10	240 mm x 101 mm x 108 mm	2.62 dm <sup>3</sup>	675.00 g

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

#### Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.