

product_datasheet_title

HALOLINE PRO 120 W 230 V R7S

HALOLINE® PRO | Double ended halogen lamps with tube base




technical_data

ELECTRICAL DATA

Nominal wattage	120 W
Construction wattage	120.00 W
Nominal voltage	230 V
Nominal current	0.52 A

PHOTOMETRICAL DATA

Luminous flux	2245 lm
Luminous efficacy	18 lm/W
Light color (designation)	Warm White
Color temperature	3000 K
Color rendering index Ra	100
Light color	1030
UV protection	No



349635_HAL_ohne_UVS

LIGHT TECHNICAL DATA

Starting time	0 s
---------------	-----

DIMENSIONS & WEIGHT

Overall length	118.00 mm
Diameter	12.00 mm
Product weight	7.2 g

LIFESPAN

Lifespan L70/B50 at 25 °C	2000 h
---------------------------	--------

ADDITIONAL PRODUCT DATA

Base (standard designation)	R7s
Mercury-free	Yes
Design / version	Tube
Product remark	Fuse protection with indicated values recommended acc. to IEC60357, EN60357 / For outdoor applications and operation in damp locations special approved fixtures are required / Technical and light values are subject to be changed

CAPABILITIES

Dimmable	yes
Burning position	Any

CERTIFICATES & STANDARDS

Energy efficiency class	G
Energy consumption	120.00 kWh/1000h

COUNTRY-SPECIFIC CATEGORIZATIONS

ILCOS	HDG-120-230-R7s-114,2
Order reference	64696 ECO

Energy labelling regulation data

Lighting technology used	OTHER
Non-directional or directional	NDLS
Mains or non-mains	MLS
Light source cap-type (or other electric interface)	R7s
Connected light source (CLS)	no
Color-tuneable light source	no
Envelope	No
High luminance light source	no
Anti-glare shield	no
Standby power	0 W
Networked standby power for CLS	not applicable
Claim of equivalent power	No
Length	118.00 mm
Height	12.00 mm
Width	12.00 mm
Chromaticity coordinate x	0,437
Chromaticity coordinate y	0,404

Beam angle correspondence	SPHERE_360
Displacement factor	1
EPREL ID	714434,1554002
Model number	AC35303,AC51810

download_data

Photometric and lighting design files	document_name
 Spectral power distribution	349635_HAL_ohne_UVS

logistical_data

product_code	packaging_unit	dimensions	weight	volume
4008321977670	Folding box 1	20 mm x 21 mm x 136 mm	15.00 g	0.06 dm ³
4058075308695	Shipping box 15	93 mm x 71 mm x 128 mm	328.00 g	0.85 dm ³
4008321977687	Shipping box 20	142 mm x 111 mm x 90 mm	278.00 g	1.42 dm ³
4058075308701	Shipping box 60	195 mm x 148 mm x 133 mm	1459.00 g	3.84 dm ³
4052899401280	Shipping box 720			
4099854147708	Shipping box 720	440 mm x 347 mm x 385 mm	10342.00 g	58.78 dm ³

logistical_data_text

disclaimer_title

disclaimer_text