OSRAM ALLSEASON SUPER / ALLSEASON H1

Extra visibility under all weather conditions







Up to 30% more light

For better visibility and significantly shorter reaction times compared to standard halogen lamps



Better sight Under all weather conditions



Better sight under all weather conditions

With up to 30% more light compared to standard lamps and an interference yellow coating ALLSEASON and ALLSEASON SUPER improve visibility while on the road under all weather conditions.

Technical data

Product information

Application (Category and Product specific)	Halogen headlight lamp

General Product Information

Global order reference	64150ALS
------------------------	----------

Electrical Data


Power input	68 W ¹⁾
Nominal voltage	12.0 V
Nominal wattage	55 W
Test voltage	13.2 V

¹⁾ Maximum

Photometric Data

Nominal luminous flux	1550 lm
Luminous flux tolerance	±15 %
Color temperature	3200 К

Physical Attributes & Dimensions



Diameter	8.5 mm
Product weight	6.30 g
Length	62.5 mm
Lamp base	P14.5s

Lifetime Data

Lifespan B3	150 hr
Lifespan Tc	350 hr

Capabilities

Technology	HAL	

Η1

Certificates & standards

ECE category

Environmental & Regulatory Information

Information according Art. 33 of EU Regulation (EC) 1907/2006 (REACh)

Primary article identifier	4050300504544 4008321168733	
Candidate list substance 1	No declarable substances contained	
Declaration no. in SCIP database	No declarable substances contained	

Country specific information

Product code	METEL code	SEG-No.	STK-Number	UK Org
4050300504544	OSRA64150ALS	-	-	-
4050300504544	OSRA64150ALS	-	-	-

- Logistical Data

Product code	Product description	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Volume	Gross weight
4050300504544	ALLSEASON SUPER / ALLSEASON H1	FS ECO 1	25 mm x 23 mm x 70 mm	0.04 dm³	8.00 g
4050300504568	ALLSEASON SUPER / ALLSEASON H1	Shipping carton box 100	245 mm x 145 mm x 140 mm	4.97 dm³	945.00 g

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

Download Data

	File
7	User instruction GPRS_Safety symbols instructions

Application advice

For more detailed application information and graphics please see product datasheet.

Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.





> 200 °C









