



# **MASTER LEDspot MV**

# MAS LEDspotMV DimTone 4-35W GU10 25D

Delivering a warm, halogen-like accent beam, MASTER LEDspot MV is a perfect fit for spot lighting (track, corridors, lift lobbies, display cases and cabinets) in the hospitality industry. It is particularly suitable to public areas where the light is on 24/7, such as lobbies, corridors, stairwells.MASTER LEDspot MV delivers huge energy savings and minimizes maintenance cost without any compromise on brightness, enabling hospitality owners to achieve a return on their investment within one year. These LEDspots are compatible with most existing fixtures with a GU10 holder and designed as a retrofit replacement for halogen or incandescent spots. The dimmable versions drive further efficiencies, while helping to create the desired atmosphere.

#### **Product data**

General Information		
Cap base	GU10 [ GU10]	
Nominal lifetime (nom.)	50000 h	
Switching cycle	50000X	
Technical type	4-35W	
Light Technical		
Colour code	822-827 [ tunable warm white]	
Beam Angle (Nom)	25 °	
Light distribution	25D [ Medium beam]	
Luminous flux (nom.)	305 lm	
Luminous flux (rated) (nom.)	305 lm	
Luminous intensity (nom.)	1000 cd	
Colour designation	Warm White (WW)	
Rated beam angle	25 °	
Correlated colour temperature (nom.)	2200-2700 K	
Luminous efficacy (rated) (nom.)	70.00 lm/W	

Colour consistency	<6
Color rendering index (nom.)	80
LLMF at end of nominal lifetime (nom.)	70 %
Luminous Flux in 90° Cone (Rated)	280 lm
Operating and Electrical	
Input frequency	50 to 60 Hz
Power (Rated) (Nom)	4 W
Lamp current (nom.)	22 mA
Starting time (nom.)	0.5 s
Warm-up time to 60% light (nom.)	instant full light
Power factor (nom.)	0.5
Voltage (Nom)	220-240 V
Temperature	
T-Case maximum (nom.)	70 °C

Datasheet, 2019, April 2 data subject to change

### **MASTER LEDspot MV**

Controls and Dimming	
Dimmable	Yes
Approval and Application	
Energy efficiency label (EEL)	A+
Suitable for accent lighting	Yes
Energy Consumption kWh/1000 h	4 kWh
Product Data	

Order product name	MAS LEDspotMV DimTone 4-35W GU10 25D	
EAN/UPC – product	8718696438282	
Order code	43828200	
Numerator – quantity per pack	1	
Numerator – packs per outer box	10	
Material no. (12NC)	929001130602	
Net weight (piece)	0.036 kg	

#### **Warnings and Safety**


Full product code

• Operating temperature range is between -20° C and 45° C ambient

871869643828200


- Only to apply in dry or damp locations and most of open fixtures with lamp-holders that offer sufficient space (10 mm free air space)
- Not intended for use with emergency light fixtures or exit lights


#### Dimensional drawing



Product	D	С
MAS LEDspotMV DimTone 4-35W GU10 25D	50 mm	55 mm

#### Photometric data





## **MASTER LEDspot MV**



© 2019 Signify Holding All rights reserved. Signify does not give any representation or warranty as to the accuracy or completeness of the information included herein and shall not be liable for any action in reliance thereon. The information presented in this document is not intended as any commercial offer and does not form part of any quotation or contract, unless otherwise agreed by Signify. Philips and the Philips Shield Emblem are registered trademarks of Koninklijke Philips N.V.